

PARSUN

Two-Stroke Engine



PARSUN OUTBOARD ENGINE

**3 Years
Warranty**

รับประกัน 3 ปี

ติดต่อ www.twineye2002.com

www.twineye.com

อาคารเทพนคร ถนนบางนา-ตราด กม.1

Tel.0-2399-3692 , 081-919-3055



Specification

MODEL	Unit	T60BEL-D	T60FEL-T	T60FEX-T	T90BEL-D	T90FEL-T	T90FEX-T
Horse power	hp	60 hp			90 hp		
Overall length	mm(in.)	1337(52.6)	726(28.6)		1337(52.6)	726(28.6)	
Overall width	mm(in.)	398(15.7)	374(14.7)		398(15.7)	374(14.7)	
Overall height	mm(in.)	1422(56.0)	1422(56.0)	1548(60.9)	1422(56.0)	1422(56.0)	1548(60.9)
Transom height	mm(in.)	508(20.0)	508(20.0)	635(25.0)	508(20.0)	508(20.0)	635(25.0)
Weight	kg	119	119	122	119	119	122
Full throttle operating range	r/min	4500-5500			4500-5500		
Maximum output	kw(HP)@r/min	44.1(60)@5000			66.2(90)@5000		
Idling speed(Neutral)	r/min	800±50			800±50		
Engine type		2-Stroke			2-Stroke		
Cylinders		L3			L3		
Displacement	cm³	1141			1141		
Bor x stroke	mm(in.)	82.0X72.0(3.23X2.83)			82.0X72.0(3.23X2.83)		
Ignition system		CDI			CDI	CDI	
Control system		Tiller control	Remote Control		Tiller control	Remote Control	
Starting system		Electric start			Electric start		
Gear positions		Forward-Neutral-Reverse			Forward-Neutral-Reverse		
Gear ratio		2.0(26/13)			2.0(26/13)		
Trim and tilt system		Hydrolic elevator	Electric tilt		Hydrolic elevator	Electric tilt	
Fuel tank capacity	L	24			24		
Maximum fuel waste	L/h	34			37		
Mixing ratio	Fuel:Oil(2T)	50 : 1					
Gear oil capacity	cm³	610			610		
Propeller options	in	3-13,5/8"x13"			3-13,1/4"x17"		